

Ref.: 454009

PUMPMASTER 2 - 1:1 RATIO GREASE PNEUMATIC PUMP WITH RIGID EXTENSIONVALVE, 185 KG DRUM TRANSFER STATIONARY PACKAGE

Packages with air operated low pressure transfer pump. The pump is designed to fit through the 2" bung opening on 50 and 205 l oil drums or to be mounted on a lid for open drums. The pump is fixed using a height adjustable bung adapter. 1:1 ratio pumps are used for a clean and efficient transfer of lubricants, from their original drum to miscellaneous portable grease and oil pumps, buckets, auxiliary tanks, etc., without the risk of lubricant contamination. An air valve or an optional pressure regulator allows the user to adjust the pump speed and the lubricant flow rate. This is useful when filling open buckets to prevent splashing or to avoid overflow when reaching the top of a container. Includes drum cover PN 418 006 and follower plate PN 417 004 for 185 kg grease drums. Instruction book: 845818.

Technical data Documentation More information

Compatible fluids	Oil, Transmission fluid, Diesel
Type	Stationary Pump Packages
Pump type	Pneumatic Piston Pumps
Components	352120, 950302, 418006, 417004.001, 362303, 950313

Technical data Documentation More information

Instruction manuals

845818 Instruction book: Pumpmaster 2 - 1:1 ratio grease pneumatic pump with rigid extension valve, 185 kg drum transfer stationary package (PDF) Download

Kit components

Code	Product
352120	PNEUMATIC PISTON OIL PUMP, PUMPMASTER 2, PM2 - 1:1, 205 L (55 GAL) DRUMS
362303	OIL HOSE, 3 M x 3/4"
417004.001	STANDARD DUTY FOLLOWER PLATE, 185 KG DRUM, 550 - 590 MM (KIT COMPONENT)
418006	STANDARD DUTY DRUM COVER, 185 KG DRUM, 565 - 610 MM
950302	AIR LINE SHUTOFF VALVE, 1/4" BSP (FF)
950313	FLUID VALVE WITH BUTTERFLY TYPE CONTROL, 3/4" BSP (FF)